

FB-1732

CONVEYOR BELT LUBRICANT



DANGER

Causes severe skin burns and eye damage. Prevention: Do not breathe dusts or mists. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. **Response:** Immediately call a poison center or doctor. Specific treatment (see Section 4 on SDS). **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or

doctor. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. **IF SWALLOWED:** Rinse mouth. DO NOT induce vomiting.

Storage: Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Additional Precautions: Corrosive! Contains potassium hydroxide.

Read SDS before using this product.

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep at temperatures between 40°F and 120°F. Do NOT freeze.

FB-1732 is a premium, concentrated water-soluble conveyor lubricant utilizing a blend of high-quality fatty acids and detergent additives to provide superior lubricity on food, dairy, and beverage conveyor lines and table top conveyors. High quality formulation helps keep tracks clean and ensures smooth operations. FB-1732 is formulated to be compliant with 21 CFR 178.3570 Lubricants with Incidental Food Contact.

DIRECTIONS FOR USE: FB-1732 is for use in dairies, food plants, beverage plants, and canneries where superior lubricity is required. Various system factors such as: water quality, length of conveyors, age and type of conveyors, speed of conveyors, weight, chain type, and product containers processed can affect performance and the required use dilution. Consult your Safe Foods Chemical Innovations' Representative for specific details on application, flow rate, and nozzle recommendations.

HARD WATER: Can be used in certain hard water conditions, with limitations, at 1:50 to 1:100 dilution in hard water.

SOFT WATER: Use at 1:150 to 1:400 dilution in soft water. Soft water is highly recommended for optimal performance.

Safe Foods Chemical Innovations

1501 E 8th Street

North Little Rock, AR 72114

501-758-8500

HEALTH	3
FLAMMABILITY	0
REACTIVITY	0
PPE	D



NET CONTENTS: 5 GALLONS ____

55 GALLONS ____

275 GALLONS ____

BATCH:

FOR INDUSTRIAL USE ONLY
NOT FOR RETAIL SALE

ID #21732

CHEMTREC EMERGENCY PHONE 1-800-424-9300

UN1760

, Corrosive liquid, n.o.s., 8, PG II
(contains potassium hydroxide)